

Toleranssit
Tolerances

Nimellinen Nominal Ø mm	Osakoko Insertion fittings		Kanavakoko Tubes and fit-on fittings		Liitospituus Fit-on/insertion length min. mm	Kulmayhde Bend Angle ± 2°
	Ulkohalkaisija Outer diameter		Sisähalkaisija Inner diameter			
	min.	max.	min.	max.		
80	78,8	79,3	80,0	80,5	25	
100	98,8	99,3	100,0	100,5		
125	123,8	124,3	125,0	125,5		
150	148,7	149,3	150,0	150,6		
160	158,7	159,3	160,0	160,6		
200	198,6	199,3	200,0	200,7		
250	248,5	249,3	250,0	250,8		
300	298,4	299,3	300,0	300,9		
315	313,4	314,3	315,0	315,9		
355	353,3	354,3	355,0	356,0		
400	398,3	399,3	400,0	401,0	50	
450	448,2	449,3	450,0	451,1		
500	498,2	499,3	500,0	501,1		
560	558,1	559,3	560,0	561,2		
630	628,1	629,3	630,0	631,2		
710	708,0	709,3	710,0	711,6		
800	798,0	799,3	800,0	801,6	100	
900	897,9	899,3	900,0	902,0		
1000	997,9	999,3	1000,0	1002,0		
1120	1117,8	1119,3	1120,0	1122,5		
1250	1247,8	1249,3	1250,0	1252,5		

SFS-EN 1506 : 1998